CHANNEL RESOURCES LTD. TSX.V: CHU

Suite 1202, 1130 West Pender Street
Vancouver, BC
CANADA V6E 4A4
Tel: +1.604.684.7098
Fax: +1.604.684.7079
e-mail: info@channelresources.ca

Mankarga 5 Significant Drill Results

As at April 16, 2012

Presented by Section line from SW to NE

(*refer to bottom of list for drilling and reporting practices)*

Hole Number		Interval (metres) From	Interval (metres) To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 1500SW					
Tan11-DD54 *Hole length 204m* *-50°/120° azimuth*		*No significant intersections*			
Tan11-DD55 *Hole length 195m* *-50°/120° azimuth*		**20.0**	**22.5**	**2.5**	**0.50**
		Hole did not intersect main zone			
Section 1400SW					
Tan11-DD56 *Hole length 201m* *-50°/120° azimuth*		**90.0**	**93.4**	**3.4**	**0.72**
		103.5	**111.0**	**7.5**	**0.67**
		159.0	**163.5**	**4.5**	**0.23**
		171.0	**174.0**	**3.0**	**0.43**
Tan11-DD57 *Hole length 297m* *-50°/120° azimuth*		**84.0**	**87.1**	**3.1**	**1.12**
		175.5	**187.5**	**12.0**	**1.14**
	includes	176.0	176.4	0.4	17.60
Section 1300SW					
Tan11-DD32 *Hole length 173m* *-50°/300° azimuth*		**0.0**	**12.5**	**12.5**	**2.34**
	includes	6.5	8.0	1.5	4.29
		90.5	**95.0**	**4.5**	**0.34**
Tan11-DD53 *Hole length 201m* *-50°/120° azimuth*		**18.0**	**25.5**	**7.5**	**0.29**
		27.0	**34.5**	**7.5**	**0.67**
		71.6	**76.5**	**4.9**	**0.62**
		94.5	**104.8**	**10.3**	**0.52**
		108.8	**115.5**	**6.7**	**0.38**
Section 1100SW					
Tan11-DD60 *Hole length 201m* *-50°/120° azimuth*		*No significant intersections*			
Section 1000SW					
Tan11-DD59 *Hole length 213m* *-50°/120° azimuth*		*No significant intersections*			
Section 900SW					
Tan11-DD58 *Hole length 201m* *-50°/120° azimuth*		*No significant intersections*			
Tan11-DD26 *Hole length 176m* *-50°/120° azimuth*		*No significant intersections*			

Hole Number		Interval (metres) From	Interval (metres) To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 800SW					
Tan11-RC55 *Hole length 120m* *-50°/300° azimuth*		*No significant intersections*			
Tan11-DD17		**59.0**	**129.0**	**70.0**	**1.99**
Hole length 202m	includes	68.0	81.5	13.5	6.47
-50°/300° azimuth		**161.5**	**164.5**	**3.0**	**1.69**
Tan11–RC72		**42**	**102**	**60**	**1.15**
Hole length 126m	includes	54	66	12	2.33
-50°/300° azimuth	and	78	86	8	2.72
Tan11-DD20		**63.5**	**65.0**	**1.5**	**1.82**
Hole length 236m		**84.5**	**89.0**	**4.5**	**0.67**
-50°/120° azimuth		**120.5**	**153.5**	**33.0**	**2.40**
	includes	141.5	143.0	1.5	19.00
		195.5	**197.0**	**1.5**	**1.05**
		206.0	**207.5**	**1.5**	**1.36**
Section 650SW					
Tan11–RC56		**96**	**134**	**38**	**2.46**
Hole length 134m	includes	122	126	4	18.40
-50°/300° azimuth					
Tan11–RC71		**8**	**64**	**56**	**1.21**
Hole length 138m	includes	56	58	2	15.55
-50°/300° azimuth		**78**	**86**	**8**	**0.15**
Section 600SW					
Tan12-DD68		**49.5**	**63.0**	**13.5**	**0.43**
Hole length 201m		**66.0**	**132.0**	**66.0**	**1.18**
-50°/120° azimuth	includes	85.5	103.5	18.0	3.27
Tan12-DD67		**114.0**	**186.0**	**72.0**	**2.12**
Hole length 273m	includes	162.0	174.0	12.0	8.66
-50°/120° azimuth					
Section 550SW					
Tan11–RC73		**110**	**158**	**48**	**2.72**
Hole length 180m	includes	122	142	20	5.76
-50°/300° azimuth		**168**	**176**	**8**	**0.16**
Tan11–RC57		**22**	**74**	**52**	**1.18**
Hole length 134m	includes	30	32	2	17.10
-50°/300° azimuth		**84**	**116**	**32**	**1.90**
	includes	102	106	4	13.37
Tan11-DD52		**138.0**	**142.5**	**4.5**	**0.26**
Hole length 255m		**145.5**	**198.0**	**52.5**	**0.74**
-50°/120° azimuth	includes	172.5	183.0	10.5	1.90
		partial hole only – based on available assay results from first 199.5 of 255.0 metres			

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 500SW					
Tan11–RC74		**60**	**72**	**12**	**0.16**
Hole length 180m		**90**	**162**	**72**	**0.74**
-50°/300° azimuth	includes	94	128	34	1.24
Tan11–RC58		**0**	**70**	**70**	**2.10**
Hole length 124m	includes	12	26	14	6.23
-50°/300° azimuth		**98**	**124**	**26**	**0.31**
Tan11-DD22		**11.0**	**35.0**	**24.0**	**0.63**
Hole length 170m	includes	14.0	15.5	1.5	3.37
-50°/120° azimuth		**63.5**	**81.6**	**18.1**	**2.05**
		87.5	**89.0**	**1.5**	**1.20**
Tan11-DD24		**8.0**	**12.5**	**4.5**	**0.27**
Hole length 260m		**20.0**	**27.5**	**7.5**	**0.56**
-50°/120° azimuth		**30.5**	**40.1**	**9.6**	**0.96**
	includes	36.5	38.0	1.5	3.25
		111.9	**119.4**	**7.5**	**1.62**
	includes	115.0	115.4	0.4	23.50
		121.8	**128.0**	**6.2**	**0.29**
		140.2	**186.5**	**46.3**	**0.43**
Section 400SW					
Tan11–RC75		**60**	**94**	**34**	**0.44**
Hole length 102m	includes	60	66	6	1.21
-50°/300° azimuth					
Tan11–RC76		**0**	**30**	**30**	**0.45**
Hole length 102m					
-50°/300° azimuth					
Section 300SW					
Tan11-RC77		*No significant results*			
Hole length 102m					
-50°/300° azimuth					
Tan11–RC87		**10**	**52**	**42**	**0.79**
Hole length 156m	includes	10	26	16	1.72
-50°/300° azimuth		**62**	**156**	**94**	**0.69**
	includes	94	96	2	9.86
	and	114	116	2	2.90
Tan11-DD29		**8.0**	**9.5**	**1.5**	**1.14**
Hole length 80m		** Hole abandoned at 80 metres due to ground conditions – target at 180 metres*			
-50°/120° azimuth					
Tan11-DD30		**104.0**	**107.0**	**3.0**	**1.56**
Hole length 272m		**113.0**	**117.5**	**4.5**	**0.27**
-50°/120° azimuth		**119.0**	**126.5**	**7.5**	**0.30**
		137.0	**146.0**	**9.0**	**0.20**
		164.0	**166.2**	**2.2**	**0.72**
		173.0	**202.6**	**29.6**	**0.41**
	includes	176.0	179.9	3.9	0.96
		195.5	**202.2**	**6.7**	**0.71**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 250SW					
Tan11–RC88		**0**	**42**	**42**	**0.39**
Hole length 42m	includes	6	16	10	0.69
Vertical Water Well					
Tan11–RC89		**18**	**28**	**10**	**0.59**
Hole length 72m		**58**	**72**	**14**	**0.41**
Vertical Water Well					
Section 200SW					
Tan11–RC59		**74**	**120**	**46**	**0.27**
Hole length 120m	includes	76	82	6	0.63
-50°/300° azimuth					
Tan11–RC60		**0**	**42**	**42**	**0.37**
Hole length 126m	includes	6	16	10	0.71
-50°/300° azimuth		**52**	**68**	**16**	**0.27**
Section 100SW					
Tan11–RC37		**32**	**70**	**38**	**0.78**
Hole length 120m	includes	36	50	14	1.46
-50°/300° azimuth					
Tan11-DD45		**0.0**	**30.0**	**30.0**	**1.28**
Hole length 139.5m		*partial hole only – based on available assay results from first 63 of 139.5 metres*			
-50°/120° azimuth					
Tan11–RC38		**6**	**14**	**8**	**0.25**
Hole length 102m		**32**	**40**	**8**	**1.03**
-50°/300° azimuth					
Section 000					
Tan10–RC19		**104**	**142**	**38**	**0.32**
Hole length 198m					
-50°/300° azimuth					
Tan10-RC7		**14**	**30**	**16**	**0.11**
Hole length 100m		**46**	**94**	**48**	**1.17**
-50°/300° azimuth	includes	52	78	26	1.98
	includes	54	58	4	3.32
	and	74	78	4	6.54
Tan12-DD70		**18.0**	**24**	**6**	**0.38**
Hole length 180m		**25.5**	**40.5**	**15**	**0.52**
-50°/120° azimuth	includes	25.5	31.5	6.0	1.13
		48.0	**70.5**	**22.5**	**0.83**
	includes	51.0	58.5	7.5	1.55
		75.0	**88.5**	**13.5**	**1.00**
		91.5	**96.0**	**4.5**	**0.27**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 100NE					
Tan11-DD36		**22.0**	**79.0**	**57.0**	**0.61**
Hole length 205m	includes	23.5	31.0	6.0	1.30
-50°/120° azimuth	and	55.0	58.0	3.0	2.46
		82.0	**92.5**	**10.5**	**0.17**
		101.5	**110.5**	**9.0**	**0.37**
		128.5	**131.5**	**3.0**	**0.47**
Section 150NE					
Tan10–RC18		**46**	**94**	**48**	**0.93**
Hole length 200m	includes	60	66	6	4.69
-50°/300° azimuth		**108**	**122**	**14**	**0.24**
Tan11-DD37		**102.5**	**162.5**	**60.0**	**0.81**
Hole length 223m	includes	137.0	143.0	6.0	2.07
-50°/120° azimuth		**170.0**	**174.5**	**4.5**	**0.28**
Section 250NE					
Tan10–RC17		**80**	**108**	**28**	**0.42**
Hole length 199.2m		**118**	**182**	**64**	**0.66**
-50°/300° azimuth	includes	134	172	38	0.88
	and	134	142	8	1.46
Tan10–DD19		**1.5**	**38.0**	**36.5**	**0.38**
Hole length 203m		**62.0**	**136.8**	**74.8**	**0.90**
-50°/300° azimuth	includes	105.5	122.0	16.5	1.58
Tan10-RC8		**8**	**32**	**24**	**0.27**
Hole length 141.5m		**58**	**141.5**	**83.5**	**0.94**
-50°/300° azimuth	includes	68	118	50	1.37
	Includes	68	78	10	3.11
	and	90	108	18	1.49
Tan10–RC16		**0**	**10**	**10**	**0.41**
Hole length 200m					
-50°/300° azimuth					
Tan11-DD21		**12.5**	**24.5**	**12.0**	**0.69**
Hole length 272m		**35.0**	**44.0**	**9.0**	**0.61**
-50°/120° azimuth		**47.0**	**119.0**	**72.0**	**1.41**
	includes	102.5	108.5	6.0	7.97
	includes	104.0	105.5	1.5	18.70
		131.0	**150.5**	**19.5**	**0.72**
Tan11-DD34		**93.0**	**100.0**	**7.0**	**0.24**
Hole length 321.5m		**113.5**	**115.0**	**1.5**	**1.05**
-50°/120° azimuth		**137.3**	**197.4**	**60.1**	**0.56**
	includes	178.0	187.0	9.0	1.17
		211.0	**232.0**	**21.0**	**0.51**
	includes	218.5	224.0	5.5	1.20

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 350NE					
Tan11-RC42		**78**	**158**	**80**	**0.70**
Hole length 158m	includes	90	118	28	1.30
-50°/300° azimuth	and	150	158	8	1.02
Tan10–RC20		**2**	**36**	**34**	**0.32**
Hole length 200m	includes	2	14	12	0.60
-50°/300° azimuth		**46**	**118**	**72**	**0.58**
	includes	70	96	26	0.99
	and	82	96	14	1.43
		166	**176**	**10**	**4.05**
	includes	166	168	2	18.70
Tan11-DD25		**0.0**	**7.5**	**7.5**	**0.64**
Hole length 201m		**15.0**	**30.0**	**15.0**	**0.29**
-65°/120° azimuth		**31.5**	**37.5**	**6.0**	**0.28**
		39.0	**97.5**	**58.5**	**1.03**
	includes	39.0	48.0	9.0	2.32
	and	60.0	66.0	6.0	1.94
Tan11-RC36		**0**	**8**	**8**	**0.24**
Hole length 116m		**14**	**24**	**10**	**0.22**
-50°/300° azimuth					
Tan11-DD23		**83.7**	**93.5**	**9.8**	**0.29**
Hole length 302m		**99.5**	**130.3**	**30.8**	**0.56**
-50°/120° azimuth		**135.2**	**150.5**	**15.3**	**0.69**
	includes	135.2	137.0	1.8	3.88
		155.0	**174.2**	**19.2**	**1.23**
	includes	162.5	170.0	7.5	2.62
		188.4	**212.0**	**23.6**	**0.63**
	includes	198.5	200.9	2.4	1.43
	and	204.5	207.5	3.0	1.73
		215.1	**219.5**	**4.4**	**0.25**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 450NE					
Tan11–RC70		**142**	**198**	**56**	**1.00**
Hole length 204m	includes	152	176	24	1.61
-50°/300° azimuth					
Tan11–RC39		**26**	**128**	**102**	**1.52**
Hole length 149.5m	includes	36	68	32	3.00
-50°/300° azimuth	and	82	96	14	1.89
Tan11-DD02		**32.0**	**140.0**	**108.0**	**1.10**
Hole length 256m	includes	40.0	60.0	20.0	2.32
-50°/300° azimuth	and	65.8	90.0	24.2	1.81
		146.0	**196.0**	**50.0**	**0.43**
	includes	158.3	159.0	0.7	7.86
		202.0	**213.0**	**11.0**	**0.38**
		219.4	**238.0**	**18.6**	**0.78**
	includes	219.4	228.0	8.6	1.20
Tan10–RC21		**0**	**66**	**66**	**0.51**
Hole length 186m	includes	36	46	10	1.47
-50°/300° azimuth		**72**	**126**	**54**	**0.70**
	includes	88	100	12	1.52
		146	**184**	**38**	**0.42**
	includes	174	180	6	1.63
Tan11-DD01		**0.0**	**64.0**	**64.0**	**0.41**
Hole length 263m		**69.3**	**168.0**	**98.7**	**0.92**
-50°/120° azimuth	includes	110.0	140.0	30.0	1.15
	and	146.0	158.0	12.0	1.94
	includes	149.5	150.0	0.5	14.90
Tan11-DD27		**35.0**	**42.5**	**7.5**	**0.25**
-50°/120° azimuth		** Hole abandoned at 96 metres due to ground conditions – target at 270 metres*			
Tan11-DD28		**9.5**	**26.0**	**16.5**	**1.49**
Hole length 323m	includes	21.5	23.0	1.5	14.40
-50°/120° azimuth		**63.5**	**65.0**	**1.5**	**2.18**
		77.0	**81.5**	**4.5**	**0.57**
		102.5	**114.5**	**12.0**	**0.32**
		125.0	**134.0**	**9.0**	**1.18**
	includes	129.5	131.0	1.5	4.17
		152.0	**156.5**	**4.5**	**0.25**
		161.0	**165.5**	**4.5**	**0.25**
		200.0	**245.0**	**45.0**	**0.68**
	includes	212.0	213.5	1.5	7.59
		251.0	**269.5**	**18.5**	**0.38**
		277.4	**303.5**	**26.1**	**0.74**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 550NE					
Tan11–RC69		**2**	**50**	**48**	**1.07**
Hole length 60m	includes	6	18	12	1.66
-50°/300° azimuth					
Tan11-DD05		**6.0**	**75.0**	**69.0**	**0.63**
Hole length 252m	includes	12.0	19.5	7.5	2.08
-50°/120° azimuth	and	40.8	45.0	4.2	1.08
	and	61.5	63.0	1.5	5.32
		80.0	**107.0**	**27.0**	**0.32**
		114.5	**128.4**	**13.9**	**0.23**
		131.4	**150.5**	**19.1**	**0.41**
		166.8	**176.2**	**9.4**	**0.24**
		200.2	**207.8**	**7.6**	**5.35**
	includes	205.5	207.0	1.5	25.30
Tan10–RC22		**0**	**38**	**38**	**0.29**
Hole length 204m		**42**	**122**	**80**	**0.35**
-50°/300° azimuth	includes	42	80	38	0.48
		140	**146**	**6**	**0.40**
Tan11-DD03		**9.0**	**61.5**	**52.5**	**1.20**
Hole length 201m	includes	36.0	40.5	4.5	5.67
-50°/120° azimuth	includes	39.0	40.5	1.5	15.10
	and	60.0	61.5	1.5	11.70
		111.0	**177.0**	**66.0**	**0.64**
	includes	144.2	145.0	0.8	8.20
	and	152.2	168.0	15.8	1.64
Tan11-DD31		**62.0**	**68.6**	**6.6**	**0.39**
Hole length 272m		**70.0**	**79.5**	**9.5**	**0.17**
-50°/120° azimuth		**101.5**	**122.0**	**20.5**	**0.40**
		136.6	**146.7**	**10.1**	**0.49**
	includes	136.6	138.5	1.9	1.18
		156.6	**161.0**	**4.4**	**0.42**
		201.5	**207.5**	**6.0**	**0.26**
		219.5	**234.5**	**15.0**	**1.20**
	includes	227.0	230.0	3.0	2.19
Section 650NE					
Tan11-RC30		*No significant results*			
Hole length 90m					
-50°/300° azimuth					
Tan11-DD04		**64.5**	**70.5**	**6.0**	**0.21**
Hole length 250m		**103.3**	**106.8**	**3.5**	**0.37**
-50°/300° azimuth		**115.5**	**180.0**	**64.5**	**0.77**
	includes	119.0	130.3	11.3	1.32
	and	161.2	166.5	5.3	2.24
		184.0	**195.0**	**11.0**	**2.73**
	includes	184.9	186.0	1.1	24.6
		203.5	**250.0**	**46.5**	**0.84**
	includes	210.5	211.0	0.5	43.60
Tan11–RC31		**52**	**86**	**34**	**0.64**
Hole length 86m	includes	72	84	12	0.92
-50°/300° azimuth					

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 650NE (Continued)					
Tan11–RC32		**52**	**82**	**30**	**0.63**
Hole length 86m	includes	70	76	6	2.23
-50°/300° azimuth					
Tan11-DD42		**1.5**	**11.0**	**9.5**	**0.68**
Hole length 168m		**15.5**	**24.5**	**9**	**0.27**
-50°/120° azimuth		**30.5**	**62**	**31.5**	**0.53**
		69.5	**90.5**	**21.0**	**1.25**
		94.5	**99**	**4.5**	**0.48**
Tan11–RC33		**0**	**12**	**12**	**0.23**
Hole length 90m		**36**	**44**	**8**	**0.51**
-50°/300° azimuth		**64**	**90**	**26**	**0.63**
	includes	74	82	8	1.28
Tan11–RC34		30	38	8	0.55
Hole length 102m		52	72	20	0.37
-50°/300° azimuth					
Tan11-DD07		**0.0**	**42.0**	**42.0**	**0.53**
Hole length 192m	includes	4.5	12.0	7.5	1.19
-50°/120° azimuth		**69.0**	**90.0**	**21.0**	**0.59**
	includes	84.0	87.0	3.0	1.41
		97.5	**106.0**	**8.5**	**0.91**
		120.0	**127.5**	**7.5**	**0.54**
		138.0	**178.5**	**40.5**	**0.55**
	includes	156.0	163.5	7.5	1.10
Tan11–RC35		No significant results			
Hole length 120m					
-50°/300° azimuth					
Tan11-DD33		**0.35**	**6.75**	**6.4**	**0.27**
Hole length 263m		**26.0**	**30.5**	**4.5**	**0.50**
-50°/120° azimuth		**62.0**	**68.0**	**6.0**	**0.46**
		77.0	**99.5**	**22.5**	**0.29**
		140.0	**152.0**	**12.0**	**0.35**
		167.0	**174.9**	**7.9**	**0.16**
		177.5	**185.0**	**7.5**	**1.02**
		201.5	**204.5**	**3.0**	**0.66**
		212.0	**239.0**	**27.0**	**1.90**
	includes	215.0	222.5	7.5	2.83
Section 750NE					
Tan11–RC40		**4**	**16**	**12**	**0.30**
Hole length 116m		**64**	**116**	**52**	**1.44**
-50°/300° azimuth	includes	86	94	8	4.81
Tan11–RC61		**2**	**18**	**16**	**1.58**
Hole length 90m		**28**	**82**	**54**	**0.39**
-50°/300° azimuth					
Tan11-DD06		**1.5**	**9.5**	**8.0**	**0.58**
Hole length 148.5m		**13.5**	**21.0**	**7.5**	**0.99**
-50°/120° azimuth		**24.0**	**78.0**	**54.0**	**0.70**
	includes	43.0	44.8	1.8	6.03
		111.8	**121.5**	**9.7**	**0.24**
		126.0	**148.5**	**22.5**	**0.25**

Hole Number	Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 750NE (continued)				
Tan11–RC85	**0**	**4**	**4**	**0.46**
Hole length 90m	**82**	**90**	**8**	**0.58**
-50°/300° azimuth				
Tan11-DD09	**32.0**	**39.5**	**7.5**	**0.43**
Hole length 204m	**59.0**	**62.7**	**3.7**	**0.71**
-50°/120° azimuth	**68.6**	**70.3**	**1.7**	**2.12**
includes	69.0	69.2	0.2	16.70
	77.0	**80.0**	**3.0**	**0.34**
	89.0	**138.5**	**49.5**	**1.07**
includes	95.0	96.5	1.5	15.40
	158.0	**174.5**	**16.5**	**0.17**
	183.5	**203.0**	**19.5**	**0.33**
Tan11-DD08	**11.0**	**15.5**	**4.5**	**0.41**
Hole length 249m	**27.5**	**30.5**	**3.0**	**0.58**
-50°/120° azimuth	**85.5**	**96.0**	**10.5**	**0.29**
	105.0	**109.7**	**4.7**	**0.38**
	117.0	**126.6**	**9.6**	**0.19**
	133.5	**157.5**	**24.0**	**0.53**
	164.8	**191.5**	**26.7**	**0.91**
	207.0	**212.0**	**5.0**	**0.35**
	214.5	**223.5**	**9.0**	**0.37**
	225.7	**231.0**	**5.3**	**0.43**
	246.0	**249.0**	**3.0**	**1.16**
Tan11-DD10	**47.0**	**63.5**	**16.5**	**0.30**
Hole length 301m	**74.0**	**90.5**	**16.5**	**0.74**
-50°/120° azimuth	**93.5**	**119.0**	**25.5**	**0.54**
	149.0	**248.0**	**99.0**	**0.75**
includes	194.0	248.0	54.0	1.19
includes	230.0	239.0	9.0	3.69
includes	231.5	233.0	1.5	13.10
	258.5	**270.3**	**11.8**	**0.31**
	284.0	**291.5**	**7.5**	**0.30**
Tan11-DD49	**61.5**	**65.0**	**3.5**	**0.84**
Hole length 356m	**84.5**	**89.0**	**4.5**	**0.33**
-50°/120° azimuth	**107.0**	**110.0**	**3.0**	**1.19**
	129.5	**134.0**	**4.5**	**0.29**
	140.0	**144.5**	**4.5**	**0.23**
	162.5	**164.0**	**1.5**	**1.70**
	170.0	**177.5**	**7.5**	**0.40**
	180.3	**189.7**	**9.4**	**0.45**
	240.5	**264.5**	**24.0**	**0.22**
	266.0	**301.0**	**35.0**	**1.25**
includes	284.0	285.5	1.5	6.49
	312.5	**339.5**	**27.0**	**0.23**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 850NE					
Tan11–RC68		**76**	**106**	**30**	**0.59**
Hole length 138m		**110**	**120**	**10**	**0.19**
-50°/300° azimuth					
Tan11-RC41		**0**	**96**	**96**	**0.44**
Hole length 96m	includes	52	64	12	1.21
-50°/300° azimuth					
Tan11–RC62		**0**	**68**	**68**	**1.07**
Hole length 90m	includes	18	54	36	1.65
-50°/300° azimuth					
Tan11-DD11		**0.00**	**116.7**	**116.7**	**0.66**
Hole length 270m	includes	31.4	60.5	29.1	1.10
-50°/120° azimuth	and	95.0	101.8	6.8	2.61
		134.0	**152.0**	**18.0**	**0.31**
		168.5	**173.0**	**4.5**	**0.34**
Tan11-DD12		**33.5**	**45.5**	**12.0**	**0.12**
Hole length 305m		**61.0**	**76.1**	**15.1**	**0.27**
-50°/120° azimuth		**90.5**	**197.7**	**107.2**	**0.60**
	includes	101.0	117.5	16.5	1.24
	and	168.5	173.0	4.5	1.61
		204.5	**225.5**	**21.0**	**0.53**
		236.0	**251.0**	**15.0**	**0.50**
		296.0	**305.0**	**9.0**	**0.17**
Section 950NE					
Tan11–RC84		**122**	**134**	**12**	**0.47**
Hole length 140m					
-50°/300° azimuth					
Tan11–RC90		No significant results			
Hole length 66m					
Vertical Water Well					
Tan11–RC66		**0**	**130**	**130**	**0.79**
Hole length 132m	includes	6	24	18	1.62
-50°/300° azimuth	and	40	46	6	5.57
Tan11-DD15		**0.0**	**23.0**	**23.0**	**1.18**
Hole length 155m	includes	11.0	12.5	1.5	11.80
-50°/120° azimuth		**32.0**	**42.9**	**10.9**	**0.36**
		47.0	**71.0**	**24.0**	**0.83**
	includes	48.5	50.2	1.7	5.80
		78.5	**86.0**	**7.5**	**0.27**
		122.0	**129.5**	**7.5**	**0.42**
		135.5	**144.5**	**9.0**	**0.13**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 950NE *(continued)*					
Tan11–RC63		**30**	**66**	**36**	**0.18**
Hole length 90m		**72**	**90**	**18**	**0.30**
-50°/300° azimuth					
Tan11-DD14		**0.0**	**10.5**	**10.5**	**0.22**
Hole length 207m		**25.5**	**39.0**	**13.5**	**0.19**
-50°/120° azimuth		**52.5**	**57.0**	**4.5**	**0.30**
		59.5	**64.5**	**5.0**	**0.28**
		67.5	**77.9**	**10.4**	**0.37**
		80.0	**141.0**	**61.0**	**0.52**
	includes	88.5	93.0	4.5	1.26
		172.5	**187.5**	**15.0**	**0.47**
		192.2	**207.0**	**14.8**	**0.18**
Tan11–RC65		**0**	**22**	**22**	**0.48**
Hole length 90m	includes	0	6	6	1.10
-50°/300° azimuth		**28**	**90**	**62**	**0.24**
Tan11-DD13		**5.0**	**20.0**	**15.0**	**0.24**
Hole length 250m		**23.0**	**92.0**	**69.0**	**0.47**
-50°/120° azimuth	includes	32.0	42.5	10.5	1.42
		105.5	**197.0**	**91.5**	**0.39**
	includes	143.0	150.5	7.5	1.03
		215.0	**222.5**	**7.5**	**0.31**
		227.0	**239.0**	**12.0**	**0.33**
Tan11-DD44		**0.0**	**10.5**	**10.5**	**0.36**
Hole length 320m		**22.5**	**24.0**	**1.5**	**1.32**
-50°/120° azimuth		**39.0**	**43.5**	**4.5**	**0.29**
		60.0	**67.5**	**7.5**	**0.16**
		71.0	**86.0**	**15.0**	**0.23**
		102.5	**110.0**	**7.5**	**0.26**
		164.0	**171.5**	**7.5**	**0.25**
		197.0	**218.0**	**21.0**	**0.43**
		228.5	**231.5**	**3.0**	**0.44**
		236.0	**240.5**	**4.5**	**0.27**
		242.0	**245.0**	**3.0**	**2.58**
		246.5	**254.0**	**7.5**	**0.19**
		297.5	**306.5**	**9.0**	**0.19**
		311.0	**320.0**	**9.0**	**0.36**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 1050NE					
Tan11–RC67		**46**	**64**	**18**	**0.86**
Hole length 126m	includes	46	54	8	1.55
-50°/300° azimuth		**84**	**110**	**26**	**0.48**
Tan11–RC64		**24**	**30**	**6**	**0.27**
Hole length 102m		**48**	**70**	**22**	**0.20**
-50°/300° azimuth		**78**	**84**	**6**	**0.25**
Tan11-DD18		**78.5**	**99.5**	**21.0**	**0.46**
Hole length 196m		**108.5**	**132.5**	**24.0**	**0.77**
-50°/120° azimuth	includes	120.5	125.0	4.5	2.39
		164.0	**180.5**	**16.5**	**0.47**
Tan11-DD16		**32.4**	**39.4**	**7.0**	**0.32**
Hole length 251m		**90.5**	**96.5**	**6.0**	**0.21**
-50°/120° azimuth		**130.3**	**135.5**	**5.2**	**0.29**
		143.0	**158.0**	**15.0**	**0.20**
		170.8	**186.5**	**15.7**	**0.33**
		222.9	**236.0**	**13.1**	**0.31**
Section 1150NE					
Tan11–RC78		**12**	**16**	**4**	**0.77**
Hole length 90m		**22**	**30**	**8**	**0.40**
-50°/300° azimuth		**82**	**86**	**4**	**0.32**
Section 1250NE					
Tan11–RC79		**36**	**40**	**4**	**0.84**
Hole length 100m					
-50°/300° azimuth					
Tan11–RC80		**52**	**60**	**8**	**0.36**
Hole length 108m		**98**	**106**	**8**	**0.73**
-50°/300° azimuth					
Tan11–RC81		**42**	**46**	**4**	**0.20**
Hole length 90m		**54**	**64**	**10**	**0.30**
-50°/300° azimuth					
Section 1300NE					
Tan12-DD62		**0**	**5.0**	**5**	**0.21**
Hole length 251m		**9.5**	**15.5**	**6**	**0.45**
-50°/120° azimuth		**47.0**	**65.0**	**18.0**	**1.77**
	includes	53.0	54.5	1.5	12.15
		74.0	**75.5**	**1.5**	**0.77**
		119.0	**122.0**	**3.0**	**0.45**
		134.0	**140.0**	**6.0**	**0.35**
		189.5	**195.5**	**6.0**	**0.23**
		213.5	**219.5**	**6.0**	**0.67**

Hole Number		Interval (metres) From	To	Intercept (metres)	Weighted Average Grade (g/t Au)
Section 1350NE					
Tan11–RC82		No significant results			
Hole length 108m					
-50°/300° azimuth					
Tan11–RC83		**56**	**76**	**20**	**0.52**
Hole length 78m	includes	66	72	6	1.03
-50°/300° azimuth					
Section 1550NE					
Tan11–RC86		**0**	**12**	**12**	**0.32**
Hole length 126m					
-50°/300° azimuth					

Channel Resources Ltd. maintains a rigorous quality control program involving the use of duplicate samples and blanks and certified gold standards from an accredited Canadian laboratory in every batch of 20 samples. Core samples are assayed using standard fire assay techniques on a 50 gram charge with an atomic absorption finish by SGS Burkina Faso SA in Ouagadougou, Burkina Faso. The drilling program is supervised by John Adams P.Geo., a qualified person as defined by NI 43–101.

Drilling, sampling and reporting practices:

- All hole collars are set to dip at -50° to their respective azimuths except hole Tan11-DD25 which, due to surface conditions, was drilled at an inclination of 65°, and vertical water wells.
- RC holes are systematically sampled at 2m intervals.
- Core holes are sampled geologically with a maximum sample interval of 1.5m (with the exception of holes Tan11-DD01 and Tan11-DD02 which have a maximum sample interval of 2.0m).
- "Significant assay results" is defined as samples, or series of consecutive samples, with grade thickness (i.e. weighted average gold grades multiplied by their intervals), of greater than 1.0.
- The amount of internal dilution (i.e. with a grade of less than 0.10 g/t Au) included in a reported mineralized interval does not exceed 10% in the case of diamond core holes and 20% in the case of reverse circulation drill holes.
- No top cut has been applied to the individual grades before weighted average grades have been calculated.
- Reported intersections are downhole lengths. True widths shall be determined once geological modeling of the zone has been completed.